

tesa® 4668

Very strong transparent polyethylene tape

PRODUCT INFORMATION

Product Description

tesa® 4668 is a polyethylene tape based on a transparent PE film and an acrylic adhesive. tesa® 4668 is a very strong tape for a wide range of applications, often used for splicing of LDPE films in constructions and house buildings.

Features:

- excellent UV resistance
- strong, ageing-resistant adhesive
- weather- and waterproof
- good abrasion resistance
- very good resistance to solvents
- approved by the Swedish Institute for Technical Approval in Construction (SITAC) for splicing of polyethylene film in constructions

Main Application

- Repairing of plastic materials both indoor and outdoor
- Repairing of greenhouses
- Sealing of plastic bags
- Splicing of filmic vapour barrier materials
- Especially designed for splicing of LDPE film in constructions/house buildings

Technical Data

■ Backing material	PE film	■ Elongation at break	500 %
■ Total thickness	140 µm	■ Tensile strength	20 N/cm
■ Type of adhesive	acrylic	■ Temperature resistance (30 min)	95 °C
■ Adhesion to steel	3.4 N/cm	■ UV-resistance	24 weeks

Properties

■ Hand tearability	o	■ Abrasion resistance	+
■ Certified according to	SITAC	■ Water resistance	++

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04668>

Page 1 of 1 / As of 08/09/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.